

## Product Data Sheet

### **PRYMOS® FIRE EXTINGUISHER-SPRAY WORKSHOP & OFFICE 650 ml**

#### **1. Preface, General Statements**

A huge fire is always small in the beginning. As long as the flames are locally bounded and have not overlapped the surroundings, a fire can be extinguished successfully with relatively little effort and means. The earlier this happens the less damage will occur, hence a quick reaction is the most important matter in fire-fighting.

An inauspiciously located fire extinguisher, which can only be used with a lot of energy and might even require reading a manual, will not allow a short response time. Accordingly it is important to have an extinguisher available immediately, **ready-to-hand** in case of emergency, **most easily activated** and with **reliable extinguishing power**. PRYMOS Fire Extinguisher Sprays meet each of these demands:

#### **- Instant Usability**

PRYMOS Fire Extinguisher Spray **WORKSHOP & OFFICE** is a ready-to-use extinguisher designed for workplaces like workshops, garages, shops, offices and studios. Its dimensions are those of a big standard spray can (650 ml) and it can easily be stored at work in a cabinet, shelf or fixed by a holder at a significant place (first-aid kit, workbench), ensuring that the fire extinguisher is easy to reach exactly where fire can arise. In case of fire the customer is able to act as fast as can be and does not lose precious seconds by looking for and getting out a bulky fire extinguisher. Recognized practice standards must, of course, be fully attended to in any case.

#### **- Simple and safe application**

PRYMOS Fire Extinguisher Spray **WORKSHOP & OFFICE** is provided with a plastic cap, which can be switched off with only little effort. The spray nozzle can be used like each standard spray nozzle, the customer thus utilizes the aerosol can intuitively and operation errors are virtually out of question. Quality controlled manufacturing ensures full capacity of operational readiness.

#### **- Extinguishing power 5A / 21B / 5F**

The power of an extinguishing system is basically determined by extinguishing agents and extinguishing techniques. PRYMOS Fire Extinguisher Spray **WORKSHOP & OFFICE** consists of high-performance foam. In the biochemical process of spraying heavy foam is developed. Its quenching effect is the deprivation of heat and separation of the reactants. This effect is supported by a homogeneous, cone-shaped geometry of the spray flow as well as the cooling effect of the liquid agent.

With its Fire Extinguisher Spray **WORKSHOP & OFFICE**, PRYMOS provides professional extinguishing technology for workplaces and offices, i.e. for non-experts in fire-fighting. Periodic maintenance or surveillance are unnecessary. Extinguishing system and filling capacity are designed for one time use; the spray should be replaced by a new original PRYMOS fire extinguisher spray after use.

The operational liability of the fire extinguisher is granted for 4 years (48 months). In Germany the depleted can has to be introduced into the recoverable substance cycle within the Dual system. Other countries are bound to different recycling systems.

## 2. Execution

Like all PRYMOS Fire Extinguishers PRYMOS Fire Extinguisher Spray **Workshop & Office** is designed in a simple 965 ml/33.96 fl oz customary aluminium spray can.

## 3. Specification

The extinguishing power of PRYMOS Fire Extinguisher Spray **WORKSHOP & OFFICE** for solid and liquid substances (fire classes A and B, polar solvents excluded) was proved by successful extinguishing of standardized unit under testing. The standard BS6165:2002 with the rating of **5A, 21B** and **5F** was recognized for solid materials like wood, paper and textiles as well as for liquid fuels and for edible oils and fats. Adequate certificates from a governmental recognized inspection authority for fire extinguishing agents and tools are available (MPA Dresden). The product can be used to extinguish fire at live electrical equipment with voltages up to 1000 Volts (provided that a minimum distance of 1 meter/3.281ft. is maintained). PRYMOS foams fulfil the DIN EN 1568 standards and are admitted to the governmental recognized inspection authority for fire extinguishing agents and tools.

## 4. Technical Data

Total volume	965 ml/33.96 fl oz
Diameter	74 mm/29.1 in
Height	280 mm/11.02 in
Weight	approx. 960g/1,984 lb
Volume (net)	650 ml/22,877 fl oz
Pressure	approx. 8.5 bars (0.9 MPa) ±5%
Discharge Distance	approx. 3 m/11.48 ft
Discharge time	approx. 22 sec.
Discharge medium	Nitrogen
Extinguishing agent	Extinguishing foam
Density:	approx. 1.12 g/cm <sup>3</sup> (20°C)
Burst pressure	38 bar
Working temperature	-5°C - +50°C/23°F - 140°F
Durability	4 years (48 months - ref. date on bottom of the can)

## 5. Description of function

By pressing the spray nozzle the extinguishing agent is released. The extinguishing effect is actively supported by the generated dispersion image.

## 6. Mode of functioning

The high-performance foam is based on an aqueous solution. By means of its heat binding capability water cools down burnt material. At the same time thermic reaction conditions are disturbed with the effect that no inflammable gases and fumes can arise. The degree of droplet dispersion determines an optimal contact surface for heat transfer. Additives change the surface tension of the water and build the film forming foam supported with pressure and geometry of the nozzle. The conflagrative reaction will be stopped by this film forming layer.

## 7. Application areas

PRYMOS Fire Extinguisher **Workshop & Office** can extinguish fires of solid materials and liquids as well as edible oils and fats. The impregnating effect of the film forming agent can also be used as a heat shield. By the cooling impact hot surfaces can thus be cooled down to a lower level.

## 8. Operation

After removing the cap the extinguishing agent can be sprayed directly - in intervals - into the fire source. Please keep a safe distance!

In case of contact with eyes or mouth flush with plenty of water immediately.

## 9. Storage

PRYMOS Fire Extinguisher Spray **Workshop & Office** should be stored at a temperature between 0°C and +35°C/+32° - 95°F. The fire extinguisher must be protected from frost and should be stored at a dry place, with easy access. No storage over +50°C/+122°F. Please do not expose to extremely fluctuating temperature ranges.

## 10. Maintenance

Special maintenance is not required. The minimum durability of the product is 4 years (48 months). Please replace the extinguisher spray by a new can after use. Even if it is not depleted, at least provide an additional spray in reserve.

## 11. Article packing

PRYMOS Fire Extinguisher Spray **Workshop & Office** (Article No. 605)

- Cardboard with 12 PRYMOS Fire Extinguisher Sprays **Workshop & Office**
- Full Pallet (660 pcs.)

## 12. Distinctive features

PRYMOS Fire Extinguisher Spray **Workshop & Office** is also available for fires fed by fats and oils (pls. also refer to PRYMOS Fire Extinguisher Spray **Gastronomy**).

PRYMOS Fire Extinguisher Spray is provided with a closing cap and control strip, easily recognizable for the customer.

## 13. Authorization

PRYMOS Fire Extinguisher Spray was examined by the MPA-Dresden according to BS6165:2002; Official approval forms from the Ministry of the Interior and the Ministry of the environment in North-Rhine-Westphalia (representative reference to the Federal Republic of Germany) for active product marketing measures are available. The extinguishing tool is identified according to German law for device- and product-security. Regulatory decrees for the packaging ordinance are strictly observed.

## 14. Miscellaneous

The mentioned national standards adhere to "Specification for small disposable fire extinguishers of the aerosol type" BS 6165:2002 and the „Association Francaise de normalisation“ NF S 61-804.

You can watch PRYMOS Fire Extinguisher Sprays in action in a video, see:

<http://www.prymos.com>

Prymos GmbH

Siemensstraße 18

D-63225 Langen